



**INNOVATIVE.
SUSTAINABLE.
PROVEN.
SILT FENCE
ALTERNATIVE.**

our maximum strength line

SILTWORM ULTRA

When your project requires a more durable solution due to increased traffic or water flow, Siltworm Ultra provides ultimate strength and durability without the premium costs. Ultra's netting is designed with a more efficient fabric weave and 1/8th opening, while maintaining the same filtration capabilities as our SD product line.

PRODUCT PERFORMANCE

based on independent test results
by Tri Environmental using ASTM 7351 standards
*Soil retention effectiveness: 97%+
Maintenance detail - sediment at 50% of material height.*

Filtration technology allows water to flow through at a controlled rate to improve water quality.

FILL MATERIAL: Recycled wood fiber weed, seed, disease and bark-free, 99%+ recycled kiln-dried/low-moisture biodegradable wood material.

SILTWORM ULTRA™

SILTWORM ULTRA NETTING SPECIFICATIONS

Material Fiber	Tubular Knit Multi-filament
Material	Polypropylene
Color	Black
Melting Point	166°C
UV Protection	Photodegradable/UV Stabilized
UV Resistance ASTM D4355	1000 Hours: 100%
Approximate Life Expectancy	24 -48 months
Specific Gravity	N/A
Chemical Reaction	Inert to most soil chemicals including Alkaline, weak acids, and salt. Static Puncture
Strength Properties	ASTM D6241 & 5035 222 PSI
Mesh Opening	1/8 inch

FILL MATERIAL SPECIFICATIONS

Grind Sizing	90% 1.5 – 2-inch grind, 10% fine grind
Wood Source	Recycled wood fiber
Properties	Weed, seed, disease and bark-free, 99%+ recycled kiln-dried/low-moisture biodegradable wood material. It is approved for beneficial reuse as fill material for erosion control devices, animal bedding, and land application after use as animal bedding.
Approximate Life Expectancy	18 – 24 months
Packaging	Shrink-wrapped & palletized with caps for indoor or outdoor storage.

SKU CONFIGURATIONS / ALL PRODUCTS PALLETIZED

9-INCH DIAMETER							12-INCH DIAMETER		18-INCH DIAMETER	
LENGTH	12'	12'	20'	24'	300'	360'	10'	180'	12'	72'
PIECES	25	28	18	15	1	1	18	1	6	1
LINEAR FEET PER PALLET	300'	336'	360'	360'	300'	360'	180'	180'	72'	72'
PALLET HEIGHT	70"	72"	80"	80"	80"	86"	96"	92"	82"	86"

*Life Expectancy will vary with your type of applications, region and local climactic conditions, and should be used as a guide only.

**Measurements are obtained from tests done in lab conditions and vary depending on accuracy of infield applications.

All information supplied is considered to be true and accurate. Any non-standard conditions that may affect the applications of the materials should be consulted with Siltworm, Inc.